

A 630



INFORMATION

features;

- 2 speed motorised raise and lower of thickness bed
- Automatic setting of thickness by digital controller
- Length of thickness bed 1200mm
- Feed system with 1 x grooved infeed roller and 2 x steel outfeed rollers
- Automatic star/delts switching
- Electromagnetic brake
- Electronically controlled feed speed 4-19 m/min
- 4 knife cutter block
- 4 point locking system of thickness bed

		A530	A630	A800
Cutter block diameter	mm	120	120	150

Number of cutters	ks	4	4	4
Length of cutter block	mm	550	650	820
Speed of cutter block	n/min	4800	4800	4800
Cutter block dimension	mm	550 x 35 x 3	650 x 35 x 3	820 x 35 x 3
Max. height of thicknessing	mm	300	300	300
Max. width of thicknessing	mm	530	630	800
Max. removal thicknessing	mm	7	7	7
Main motor power	kw	5,5	7,5	11
Motor power of feeding	kw	1,1	1,1	1,5
Feeding speed	m/min	4.-19	4.-19	4.-19
Supply / frequence	V/Hz			
Length of worktable	mm	1200	1200	1200
Machine length	mm	1250	1250	1250
Machine width	mm	1050	1150	1320

Machine height	mm	1222	1222	1222
Weight	kg	1020	1160	1380

Options

- Tersa cutterblock
- Increased motor power
- Sectional infeed roller
- Rollers in thickness bed

£10,050 exc. VAT

**Download this
page as a PDF**

See all items in...

- **Thicknessers...**