

A 800



INFORMATION

features;

- 2 speed motorised raise and lower of thickness bed
- Automatic setting of thickness by digital controller
- Length of thickness bed 1200mm
- Feed system with 1 x grooved infeed roller and 2 x steel outfeed rollers
- Automatic star/delts switching
- Electromagnetic brake
- Electronically controlled feed speed 4-19 m/min
- 4 knife cutter block
- 4 point locking system of thickness bed

		A530	A630	A800
Cutter block diameter	mm	120	120	150

Number of cutters	ks	4	4	4
Length of cutter block	mm	550	650	820
Speed of cutter block	n/min	4800	4800	4800
Cutter block dimension	mm	550 x 35 x 3	650 x 35 x 3	820 x 35 x 3
Max. height of thicknessing	mm	300	300	300
Max. width of thicknessing	mm	530	630	800
Max. removal thicknessing	mm	7	7	7
Main motor power	kw	5,5	7,5	11
Motor power of feeding	kw	1,1	1,1	1,5
Feeding speed	m/min	4.-19	4.-19	4.-19
Supply / frequence	V/Hz			
Length of worktable	mm	1200	1200	1200
Machine length	mm	1250	1250	1250
Machine width	mm	1050	1150	1320

Machine height	mm	1222	1222	1222
----------------	----	------	------	------

Weight	kg	1020	1160	1380
--------	----	------	------	------

Options

- Tersa cutterblock
- Increased motor power
- Sectional infeed roller
- Rollers in thickness bed

£13,330 exc. VAT

**Download this
page as a PDF**

See all items in...

- Thicknessers...