

NANO 60 ECO



INFORMATION

The Nano series of briquetters are designed specifically for those who have a limited working space and are looking to convert a low volume of waste by either manually introducing the waste into the hopper or, as this is of a compact design, could be sited directly below a dust extraction unit.

DESCRIPTION:

Height 1065 mm, Length 1500 mm, Depth 900 mm, Weight Kg 450.

CHARACTERISTICS:

- Hydraulic Machine.
- Briquette Diameter 60 mm.
- Motor 5.5 Kw IE-2 (High Efficiency).
- Output 15/70 Kg/h.

- Octagonal drum about Ø 750 mm.
- N° 7 cycles/min.
- N° 3 cylinders.
- N° 1 vice without spacers .
- Briquette's length max 60 mm.
- Timed pre-heating device for operating in cold climates.
- Electronic manometer for pump pressure.
- Tapping head.
- Viewing windows.
- Cycle and device.
- Sensitive probe.
- Probe for the level of the oil and of the temperature.
- Power panel with PLC Touch Screen SIEMENS.
- Voltage 400V – 50 Hz.
- Use and maintenance manual.
- Service Keys.

NOTES:

N.B.: The values indicated are purely indicative and may vary depending on the kind of material.

The constructor reserves the right to make changes at any moment.

POA

PLEASE ENQUIRE FOR THE LATEST PRICING & AVAILABILITY INFORMATION FOR THIS ITEM

Download this
page as a PDF

See all items in...

- Briquetters...