

## TYPE R 630



## INFORMATION

### STANDARD EQUIPMENT

- Work table length 3050 mm
- Size of fence 1500x180 mm
- Tiltable fence 0°-45°
- Cutterhead D=120 mm, 4 knives
- Automatic star/delta switch
- Automatic table height adjustment
- Electronic measuring of cut depth
- Upper control panel
- SUVAMATIC foldable cutterhead guard
- Electromagnetic brake
- Exhaust outlet D=150 mm
- Knife setting device with indicator
- CE certification

### OPTIONAL EQUIPMENT

- Auxiliary fence for processing narrow workpieces
- Tersa cutter clock 430, 530 or 630
- Grooved table
- Extra set of knives for standard 4-knife cutterhead R 430, R 530 or R 630 HSS18%W

<b>R</b>		<b>430</b>	<b>530</b>	<b>630</b>
Length of work table	mm	3050	3050	3050
Width of work table	mm	450	550	650
Max. working width	mm	430	530	630
Diameter of cutterblock	mm	120	120	120
Number of cutters	ks	4	4	4
Speed of cutterblock	ot./min	4700	4700	4700
Max. removal	mm	5	5	5
Motor power	kW	5,5	5,5	5,5
Speed of motor	rpm	2880	2880	2880
Exhausting diameter	mm	150	150	150
Recomended min. power of exhausting	m <sup>3</sup> /hr	1800	2000	2500
Speed of exhausted air	m/s	22	22	22
Dimension of machine	mm	3050/1370/1200	3050/1470/1200	3050/1570/1200
Weight	kg	530	570	620

£9,860 exc. VAT

**Download this page as a PDF**

**See all items in...**

- **Surface planers...**